

3652RK Creative Touch 3-Series 65" interactive flat panel display





- Advanced interaction and collaboration Display Share interactive wireless collaboration toolset
- Advanced touch technology Pen and finger recognition for a seamless experience
- Picture-in-picture (PiP) Run the software solutions you know and love from your laptop whilst seamlessly annotating in Creative Board
- Safe and secure viewing experience Anti glare and anti finger print, low blue light and flicker free TUV certified

Robust collaboration, extensive connectivity options and a valuefocused design. Combining the latest technology and packed with everything a classroom or business requires, the Creative Touch 3-Series delivers all the functionalities and processing power needed to create, educate and collaborate.



Easily access the front-facing ports for HDMI and USB connectivity. For wireless connectivity, Optoma's CreativeCast Pro allows up to four users to share content at the same time from their Windows, iOS, macOS, Chrome or Android device.

Specifications

JPC: 796435 69 043 4, EAN: 50 Display	
Back light	Direct type LED
Size (diagonal)	65"
Resolution	3840x2160
Brightness	400
Contrast ratio	1,200:1
Contrast ratio (dynamic)	5,000:1
/iewing angle Response time	178° 8ms
life	50,000 hours
Display colours	1,070
Speaker count	2
Watts per speaker	20W
Surface hardness	7H
Glass	Anti Glare + Anti Finger Print
laze	4-8%
Ambient light sensor	Yes
Air gap	4.00mm
Pencil hardness	9H
Physical spec	
Dimensions (W x D x H) mm	1512 x 922 x 115
Vall-hanging screw spec	M8*25mm
/ESA holes	600x400 European Standard Dawer Cord EM
n the box	European Standard Power Cord 5M American Standard Power Cord 5M
	British Standard Power Cord 1.8M
	USB touch Cable 3M
	USB-C Cable 2M HDMI Cable 5M
	Writing Pen x2
	Remote Control
	Battery
	Pen holder/ Pen tray QSG
Connections	Inputs 3 x HDMI 2.0, 1 x VGA, 1 x DisplayPort, 1 x Audio
	3.5mm, 3 x USB 2.0, 2 x USB 3.0, 1 x RJ45, 1 x USB-C, 1 x
	Microphone, 1 x OPS slot
	Outputs 1 x HDMI 2.0, 1 x S/PDIF, 1 x Audio 3.5mm, 1 x
	RJ45
	Control 2 x USB-B interactive, 1 x RS232
Bezel size (top)	22.00mm
Bezel size (bottom)	54.00mm
Bezel size (left)	22.00mm
Bezel size (right)	22.00mm
Operating conditions	20% ~ 93% RH
Operating temperature (min)	-10°C
Operating temperature (max)	45°C
Net weight	39 kg
Gross weight	50 kg
Wireless - technology	Wifi 6, 2.4G/5G, 2T2R, BT5.2 (AZ832-HN optional)
Wireless - operating frequency	2.4G/5G
Fouch system Sensing type	IB
System	ін Windows10/Windows8/Windows7/Windows XP /Linux -
	Debian 10/Mac (1 Touch point only)/Android/Chrome
Fouch accuracy	<1.00mm
Fouch point	20 android / 40 windows
Fouch tool	Finger, Passive infrared pen
Pen/finger detection	Yes
Power	
Power supply	100-240V~ 50/60Hz 3.5A
Power consumption (standby)	0.5W
Power consumption (max)	300W
Power consumption - average	145.7
watts)	126
Power consumption - Energy Star (watts)	136
Operation System	
	Android 13
System version	Quad-core A55
System version CPU	
	Dual-core A52
CPU	Dual-core A52 4GB
GPU GPU	
CPU GPU RAM	4GB
CPU GPU RAM Storage	4GB 32GB







Copyright © 2024, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 29112024080611